

Electrics	
Description (including Dimensions and Specification)	OEM Part Number
Control rack	
Basics	
Roof fan, 230 VAC	B467111499
Plug, CH type 12, Ø11.5, LNPE, 10 A, 250 V	B4704161HA
Outlet filter, 323 x 323	B46711149N
Interface, D-sub to term block, male, 44p	B4720626CD
Interface, D-sub to term block, male, 44p	B4720626CD
Interface, D-sub to term block, male, 1x44 + 8x9	B4720692CD
Relay, 3pdt, 24 VDC, 50 mA, 700-HA33Z24D-3	B4782101HC
Relay socket, 11 pins	B4782351HC
PLC interface terminal, with relay, 24 VDC	102006995
Pressure measurement	
Measurement relay, spdt, 2--10 VDC, 24 VDC	B4792150GG
Heaters	
Thermocouple input module, -200...+1820°C	102043870
ESQ blow-out delay	
Time module, 24--240 VAC/DC, 0.1s--10h	B4782301HC
Extensions	
E-gun controller, EEC 300 (No 1)	BGM45813
Remote control, ER 030	BG438160-T
Supply distributor, AP 300	BG438260-T
E-gun CPU, EP 300	BG438210-T
EPROM set for EEC 300	BG438258-T
Memory, EPROM, TMS27C040-10JL, 4M, TI	B5088962LN
E-gun controller, EC 300	BG438230-T
Fuse link, 5x20, T, 250 V, 3.15 A	B4666446
Plastic filter, with filter mat, 99 FFB	B5099154BG
VME J1 bus PC board, 50510-105-0100	B5278841EE
Fuse link, 5x20, T, 250 V, 3.15 A	B4666446
Fuse link, 5x20, T, 250 V, 10 A	B4666456
Controller, KHAN NT (No 2)	
M module, input, 12 bit, analog, no DC	B5278804EU
Adapter: 16 volts in, ground	B5278804EV
M module, output, 12 bit, analog	B5278804EY
EMO button, front mounted (No 3)	BG596568-T
LCD display, TFT 15, IP54, 19"/66 mm (No 4)	102023603
Keyboard, Windows 95, 104 keys, USA layout (No 5)	B5278503NQ
Deposition controller, XTC/B (No 6)	B8199999AV
Deposition controller, XTC/B	B8199999DX
Crystal interface	B8199999DY
Cable, controller-oscillator, 9.1 m (30 feet)	102085961
Ink jet color printer, DeskJet 970Cxi, EN (No 7)	102075598
Multipoint socket strip (No 8)	BG531804-T
Optical interface, OI 310 (No 9)	BG438218-T